

LF rod Antenna MX

The LF rod antenna MX in the gray standard housing is a universally applicable and very compact solution for the LF range. The antenna is offered with a variable connector assembly. You can choose between Lemo standard connector, straight or angled and SMA connector. The cabling is done with a PVC cable, black. We offer different cable lengths.

RFID Antennas Frequency: 134,2 kHz


- » Convenient plug-in connections for immediate use (push-pull system)
- » Robust connectors for secure connections
- » Different types and cable lengths available
- » Compatible with HERMOS RFID readers (base LF)

Cable type

- » PVC black, temperature range from -35 / +80°C
- » Flex cable available for drag chains
- » Antenna housing: standard, max. reading range < 250 mm (depending on transponder type)

Connection options

- » Cable eyelets for screwing on
- » Open end, on request pre-assembled with Lemo standard connector, straight or angled or SMA connector



Part number	Description		
	Housing	Plug type	Length
HRF.A.LFX.SMX.LS.xx	Standard housing	LEMO 1S	xx = connection cable in dm
HRF.A.LFX.SMX.SS.xx	Standard housing	SMA	xx = connection cable in dm
HRF.A.LFF.SMX.LS.xx	Standard housing	LEMO 1S	xx = connection cable in dm Flex cable
HRF.A.LFF.SMX.SS.xx	Standard housing	SMA	xx = connection cable in dm Flex cable

(Further variants and customer-specific configurations available on request)

Technical data

Design: rod antenna
 Length antenna cylinder: 85 mm
 diameter antenna cylinder: 15 mm
 diameter antenna cable: 4,1 mm
 Antenna material: PP, light gray
 frequency: 34,2 kHz
 Cable sheath: PVC

Cable length:
 Connector type:
 Operating temperature:
 Storage temperature:
 Permissible humidity:
 Conformity:

Variant dependent
 depending on variant
 0 °C to 50 °C
 -25 °C to 70 °C
 at 50°C 25% to 80%
 RoHS, REACH

